


General Specification :

- Lead Wire: UL Type
(+)Red (-)Black
- Operation Temperature :
Temperature: -10°C~+70°C
Humidity: 35%~85%RH
- Store Temperature :
Temperature: -40°C~+70°C
Humidity: 35%~85%RH

Motor Protection :

- Impedance Protected
- Reverse Polarity Protected

Performance Curves



Item No.	Bearing System	Rated Voltage (V DC)	Rated Current (AMP)	Input Power (Watt)	Fan Speed (RPM)	Air Flow (CFM)	Static Pressure (MM-H ₂ O)	Noise Level (dBA)	Dimension (mm)
CC4010L05S CC4010L05D CC4010L05SH	Sleeve 2-Ball Hydraulic	5V	0.10	0.35	4,000 ± 10%	4.20	1.60	21	40 X 40 X 10
CC4010M05S CC4010M05D CC4010M05SH	Sleeve 2-Ball Hydraulic	5V	0.12	0.45	5,000 ± 10%	5.20	2.00	24	40 X 40 X 10
CC4010H05S CC4010H05D CC4010H05SH	Sleeve 2-Ball Hydraulic	5V	0.14	0.60	6,000 ± 10%	6.40	2.80	28	40 X 40 X 10
CC4010L12S CC4010L12D CC4010L12SH	Sleeve 2-Ball Hydraulic	12V	0.04	0.48	4,000 ± 10%	4.20	1.60	21	40 X 40 X 10
CC4010M12S CC4010M12D CC4010M12SH	Sleeve 2-Ball Hydraulic	12V	0.05	0.60	5,000 ± 10%	5.20	2.00	24	40 X 40 X 10
CC4010H12S CC4010H12D CC4010H12SH	Sleeve 2-Ball Hydraulic	12V	0.07	0.84	6,000 ± 10%	6.40	2.80	28	40 X 40 X 10
CC4010L24S CC4010L24D CC4010L24SH	Sleeve 2-Ball Hydraulic	24V	0.03	0.72	4,000 ± 10%	4.20	1.60	21	40 X 40 X 10
CC4010M24S CC4010M24D CC4010M24SH	Sleeve 2-Ball Hydraulic	24V	0.04	0.96	5,000 ± 10%	5.20	2.00	24	40 X 40 X 10
CC4010H24S CC4010H24D CC4010H24SH	Sleeve 2-Ball Hydraulic	24V	0.05	1.20	6,000 ± 10%	6.40	2.80	28	40 X 40 X 10